

Roto Gravure Printing Machine

Laminating Machine

Coating Machine

Slitting Machine

Rewinding Machine

S.A. **EG 1300**



SAM prints what you are imaging



SPECIFICATIONS

DESCRIPTION		STANDARD	NONSTANDARD
Kind of Web		OPP.CPP, PET, PE, NYLON, CELLOPHANE and The Other Flexible Films, Paper(30~80gr/m ²), Al-foil, Etc.	
Nos of Color		1~10 Colors	Separate or Double Face
Guide Roll Width		1300mm	700~1300mm
Operating Speed		20~150m/min	
Machine Control System		Semi Automatic Control System	Fully Automatic Control System
Unwinder	Type	2 Shafts Turret Type	2 Shaft Fixed Type
	Reel Dia	600mm	800mm
	Shaft	Air Fix Shaft Type	Taper Cone with Screw Type
	Tension Control	Fully Automatic Control System with A.C Vector Motor	
Infeeding Unit		Synchronized Control Type with A.C Vector Motor	
Printing Unit	Cylinder Size	D(130~300mm), L(700~1250mm)	D(130~300mm), L(400~1500mm)
	Chucking Type	Pneumatic Shaftless Locked Type	Shaft Type
	Impression Type	One Roll Pivot Arm Type	
	Drying	Heat Exchanging Type with Steam Convector	Electric/Hot Oil Heater/Gas
	Register	All Automatic with Color Controller and Compensating Roll	Pre-setting Device
Outfeeding Unit		Synchronized Control Type with A.C Vector Motor	P.I.V Control Type
Rewinder	Type	2 Shafts Turret Type	
	Reel Dia	600mm	800mm
	Shaft	Air Fix Shaft Type	Taper Cone with Screw Type
	Tension Control	A.C Vector Motor Control System	

